BEMIX

SAFETY DATA SHEET Bemix A3 FF

The safety data sheet is in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued	14.11.2018
Revision date	04.04.2024

1.1. Product identifier

Product name	Bemix A3 FF
UFI	25S7-20RN-H00A-RGAV
Article no.	1100090, 1100095, 1100230
GTIN No.	7331933522820, 7331933714287

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product group	Dry mortar of the type expander mortar.
Use of the substance / mixture	The product contains antifreeze for castings down to -10 $^\circ$ C.
Main intended use	PC-CON-4 Mortars
Uses advised against	The product may not be used in any other way than the intended use as described above.
Professional use	Yes

1.3. Details of the supplier of the safety data sheet

Company name	Finja Bemix AB
Office address	Finvids väg 6, Upplands Väsby
Postal address	Box 421
Postcode	194 04
City	Upplands Väsby
Country	Sverige
Telephone number	+46104559500
Email	info@bemix.se
Website	www.bemix.se
Enterprise No.	556117-3377

1.4. Emergency telephone number

Emergency telephone

Telephone number: In case of emergency - Call 112 and request poison information. In less urgent cases, call 010-455 95 00, Monday-Friday 7:00 a.m. 3:30 p.m.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS]	Skin Irrit. 2; H315
	Eye Dam. 1; H318
	STOT SE 3; H335
Substance / mixture hazardous properties	The product is classified as irritating to eyes, skin and by inhalation. Risk of serious eye damage. Inhaling cement dust can irritate the mucous membranes in the nose and throat. In contact with moist skin and mucous membranes, the product becomes corrosive. The product is not classified as flammable. The product is not classified as environmentally hazardous.

2.2. Label elements

Hazard pictograms (CLP)	
Composition on the label	Portlandcement*, Sand containing quartz (SiO2)**, Sodium nitrate
Signal word	Danger
Hazard statements	H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation.
Precautionary statements	P280 Wear protective gloves / protective clothing / eye protection / face protection. P362+P364 Take off contaminated clothing and wash it before reuse. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor / physician if you feel unwell.
2.3. Other hazards	
PBT / vPvB	The product, assessed based on available data, does not contain PBT substances (very persistent/bio accumulative/toxic) or vPvB substances (very persistent and very bio accumulative) according to Regulation (EC) No. 1907/2006 (REACH) Annex XIII.
Other hazards	This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Composition type	Mixture			
Substance	Identification	Classification	Contents	Notes
Portlandcement*	CAS No.: 65997-15-1 EC No.: 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	30 -40 %	
Sand containing quartz (SiO2) **	CAS No.: 14808-60-7 EC No.: 238-878-4		50 -70 %	
Sodium nitrate	CAS No.: 7631-99-4 EC No.: 231-554-3	Eye Irrit. 2; H319 Ox. Sol. 2; H272	1 -3 %	
Remarks, substance	* The Portlandcement is reduced Cr (VI) and consequently the H317 is not applicable for this product. **The classification of quartz depends on the amount of irreparable crystalline quartz. The sand used in this product contains < 1% repairable crystalline quartz and is consequently not classified as harmful to health.			

SECTION 4: First aid measures

4.1. Description of first aid measures

General	Seek medical attention and show this safety data sheet.
Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash nose, mouth and throat with water. Get medical advice/attention if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).
Eye contact	Flush immediately with plenty of water or saline for at least 15 minutes. If possible, remove contact lenses. If irritation persists: Contact a doctor. Continue to rinse during transport to the hospital/doctor.
Ingestion	Give several small portions of water to drink. Do not induce vomiting Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Acute symptoms and effects	Can cause severe irritation. The product has a drying effect on the skin. If it comes into contact with the eyes, it can cause severe irritation or caustic damage. Risk of serious eye damage.
Delayed symptoms and effects	Has an irritating effect on the mucous membranes of the respiratory tract. Long-term exposure to high concentrations of quartz can cause lung changes (silicosis).

4.3. Indication of any immediate medical attention and special treatment needed

Separate first aid equipment	Eyewash must be available.
Other information	Always get medical attention if symptoms remain. Don't give anything
	through the mouth to an unconscious person. Follow the advice given in section

4.1.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing agents suitable for the surrounding fire.
Improper extinguishing media	No special recommendations.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	The product is not classified as flammable or combustible.
----------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	During all firefighting suitable protective equipment should be used. Protective suit covering the whole body and fresh air mask is recommended.
Other information	The product is not classified as flammable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Avoid contact with respiratory system, skin or eyes. Use appropriate
	protective equipment see section 8.

6.2. Environmental precautions

Environmental precautionary	Avoid spreading dust. Avoid spreading to drains and waterways.
measures	

6.3. Methods and material for containment and cleaning up

Containment	Contain and collect spills with non-combustible absorbent materials (e.g. sand, earth, vermiculite) and place in containers for further handling of waste in accordance with current local/national regulations.
Clean up	Dry product is preferably vacuumed up with industrial vacuum cleaners. Wet product can be scooped up.
Other information	Collected material can be mixed with water for curing. Cured product is not aggressive or reactive. Dry powders are treated as hazardous goods.

6.4. Reference to other sections

Other instructions Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

Transported/handled in original packaging or in another suitable container.

Mixing should take place outdoors or in well-ventilated environments.

Protective safety measures

Protective safety measures	The workplace must have access to an eye shower with tempered water. Wash the skin after each shift, before meals, smoking and going to the toilet. No eating or drinking in the workplace.
7.2. Conditions for safe stor	age, including any incompatibilities
Storage	Store dry. Corrosive effect if product is moist. To reduce the risk of sensitization due to chrome the cement contains a low amount of Cr(VI). This effect remains 6 months after the packaging date if the product is stored according to instructions. Use of the product after this recommended time limit there is an increased risk of sensitization. Danger points apply only when the powder is moist.
Conditions for safe storage	
Requirements for storage rooms and vessels	Store in a dry place. Store in a closed container.
7.3. Specific end use(s)	
Recommendations	For additional product information, also see the technical data sheet.

SECTION 8: Exposure controls / personal protection

Comments if preventive industrial
medical examinations are to be
carried outMedical control - quartz (fibrosis-causing dust) every three years. Medical checks
in working life (AFS 2019:3)

8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Dust, inorganic		Country of origin: Sweden Limit value type: NGV Limit value (8 h) : 5 mg/m ³ Source: AFS 2018:1 Particle fraction: Inhalable Country of origin: Sweden Limit value type: NGV Limit value (8 h) : 2,5 mg/ m ³ Source: AFS 2018:1 Particle fraction: Respirable	
Quartz	CAS No.: 14808-60-7	Country of origin: Sweden Limit value type: NGV Limit value (8 h) : 0,1 mg/ m ³ Exposure limit letter Letter description: C, M Source: AFS 2018:1	

8.2. Exposure controls

Safety si	gns	
		©+ T

Precautionary measures to prevent exposure

Appropriate engineering controls	Avoid dusty handling. Use good general ventilation and local process ventilation if there is a risk of dust formation.
Eye / face protection	
Suitable eye protection	At risk of direct contact or splashing use tightly sealed safety glasses.
Hand protection	
Skin- / hand protection, short term contact	Protective gloves must be used if there is a risk of skin contact during preparation and use.
Suitable materials	Natural rubber, neoprene or PVC.
Skin protection	
Suitable protective clothing	In case of contact with wet product, waterproof clothing and shoes should be used.
Respiratory protection	
Respiratory protection necessary at	In case of brief exposure to dust use respiratory filter device with particle filter P3. In case of intensive or longer exposure use self-contained respiratory protective device
Thermal hazards	
Thermal hazards	Not applicable for the product.
Hygiene / environmental	
Personal protection equipment, comments	Wash contaminated clothes after use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Gray powder
Colour	Grey
Odour	Faint
рН	Status: In aqueous solution Value: 12

Melting point / melting range	Reason for waiving data: Not applicable
Boiling point / boiling range	Reason for waiving data: Not applicable
Flash point	Reason for waiving data: Not applicable
Flammability	The product is not flammable.
Vapour pressure	Reason for waiving data: Not applicable
Vapour density	Reason for waiving data: Not applicable
Bulk density	Value: 1500 ~ 1700 kg/m³
Solubility	Medium: Water Method: Mixable Comments: Hardens when in contact with water.
Partition coefficient: n-octanol/ water	Reason for waiving data: Not applicable
Auto-ignition temperature	Reason for waiving data: Not applicable
Decomposition temperature	Reason for waiving data: Not applicable
Viscosity	Reason for waiving data: Not applicable
Explosive properties	Not explosive
Oxidising properties	Not applicable

9.2. Other information

Other physical and chemical properties

Physical and chemical properties	Reacts with water, forms high pH, solidifies under some (harmless) heat
	development.

9.2.2. Other safety characteristics

Miscibility	Miscible with water.
Comments	Cured material is no longer reactive or aggressive

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Reacts with damp/water and forms calcium hydroxide which gives the mixture a high pH. The product reacts with water and hardens
10.2. Chemical stability	

Stability

The product is stable if used according to supplier instructions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid Avoid moisture.

10.5. Incompatible materials

Materials to avoidAvoid contact with water except when using the product according to
supplier instructions. Avoid acids, ammonium salts, aluminum or other
non-precious metals as the product contains cement.

10.6. Hazardous decomposition products

Hazardous decomposition	None known.
products	

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Other information regarding health hazards

Assessment of skin corrosion / irritation, classification	If the produkt is moist it can be corrosive due to the high pH and consequently there is a risk of corrosive damage at long term contact with moist product or wet skin
Assessment of eye damage or irritation, classification	Can cause corrosive damage, both as dry powder and wet mixture. The product is not classified as causing eye damage or irritation.
Assessment of respiratory sensitisation, classification	The product is not classified as respiratory sensitization. May bee irritating to the respiratory system and mucous membranes.
Assessment of skin sensitisation, classification	The product is not classified as sensitizing. Contains traces of chrome. May cause allergic effects on already sensitized (chrome allergic) persons
Inhalation	Can lead to chronic problems.
Skin contact	Dry skin and dry cracks. Dust can irritate the respiratory system.
Eye contact	Permanent eye damage, corrosive.
Ingestion	Irritates the oral cavity, mucous membranes and digestive system.
Sensitisation	Contains traces of chromium. Which can cause allergic problems for already sensitized people.
Assessment of germ cell mutagenicity, classification	This product is not classified as mutagen.
Assessment of carcinogenicity, classification	This product is not classified as cancerogen.
Assessment of reproductive toxicity, classification	This product is not classified as toxic for reproduction.

Symptoms of exposure

In case of ingestion	Coughing and burning.
In case of skin contact	Itchy and reddened skin. In case of contact with wet product, wounds and corrosion damage may occur.
In case of inhalation	Cough and dry throat.

In case of eye contact	Irritating, stinging and watery eyes. May cause pain.
11.2 Other information	
Endocrine disruption	This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.
SECTION 12: Ecological	information
12.1. Toxicity	
Ecotoxicity	The product is not classified as environmentally hazardous. Ecological data for the product are not available available.
12.2. Persistence and degra	adability
Persistence and degradability description/evaluation	Biologic biodegradability is not relevant for inorganic substances.
12.3. Bioaccumulative potential	
Bioaccumulation, comments	No data known.
12.4. Mobility in soil	
Mobility	No information available for the product.
12.5. Results of PBT and vF	PvB assessment
Results of PBT and vPvB assessment	The product, assessed on the basis of data, does not contain PBT substances (non-degradable/bio accumulative/toxic) or vPvB substances (very persistent and very bio accumulative) according to Regulation (EC) No. 1907/2006 (REACH) Annex XIII.
12.6. Endocrine disrupting	properties
Endocrine disrupting properties	This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.
12.7. Other adverse effects	
Additional ecological information	Contact with water gives an pH which can be toxic for water living organisms.
SECTION 13: Disposal co	onsiderations
13.1. Waste treatment meth	nods
Appropriate methods of disposal for the chemical	Uncured product is classified as harmful waste bur cured product is handled as construction waste. It is the company that produce the waste that shall define a suitable waste code connected to industrial sector and process.
Appropriate methods of disposal for the contaminated packaging	Packages that are not properly emptied must be disposed of as the unused product. Empty packaging is disposed of according to the recycling system, if

product. Empty packaging is disposed of according to the recycling system, if

	possible. The waste is handled according to official and local regulations.
EWC waste code	EWC waste code: 101314 waste concrete and concrete sludge Classified as hazardous waste: No
	EWC waste code: 200115 alkalines Classified as hazardous waste: Yes
EWL packing	EWC waste code: 150102 plasticpackaging Classified as hazardous waste: No
	EWC waste code: 150106 mixed packaging Classified as hazardous waste: No

SECTION 14: Transport information

Dangerous goods

No

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

National regulations	Hygienic limit values (AFS 2018:1) Chemical Hazards in the Working Environment (AFS 2011:19) Waste Ordinance (SFS 2020:614) Quartz – stone dust in the work environment (AFS 2015:2)
Biocides	No
Nanomaterial	No
Legislation and regulations	Position Paper Classification and labeling of crystalline silica (fine fraction), IMA Europe, May 2020. NEPSI Good Practice Guide -https://guide.nepsi.eu/ - The guidance is aimed at producers and users of products and raw materials containing crystalline silica.

15.2. Chemical safety assessment

SECTION 16: Other information

Supplier's notes

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product

	properties in terms of statutory warranty requirements. This version of the safety data sheet supersedes all previous versions.
List of relevant H-phrases (Section 2 and 3)	H272 May intensify fire; oxidiser. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Last update date	04.04.2024
Version	4